

LITHIUM COMPLEX EP2

MULTI-PURPOSE HIGH TEMPERATURE GREASE

PREMIUM GREASE TECHNOLOGY

HIGH PERFORMANCE GREASE DEVELOPED FROM DECADES OF EXPERIENCE IN CONJUNCTION WITH ORIGINAL EQUIPMENT MANUFACTURERS.

THE USE OF OUR PROPRIETARY BASE OIL TECHNOLOGY, ALONG WITH INNOVATIVE ADDITIVE CHEMISTRY GUARANTEES LONG GREASE LIFE WITHOUT ANY COMPROMISE OF EQUIPMENT RELIABILITY.



APPLICATIONS

UNIVERSAL PRODUCT DESIGNED FOR NORMAL, SEVERE DUTY, HIGH TEMPERATURE AND/OR WATER RESISTANT APPLICATIONS WHERE LITHIUM COMPLEX THICKENED NLGI #2 GREASE IS REQUIRED. SUCH SYSTEMS ARE COMMONLY FOUND IN AUTOMOTIVE, COMMERCIAL VEHICLE, MOBILE PLANT, CONSTRUCTION AND AGRICULTURAL EQUIPMENT.

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & GRADE BEFORE USE.

KEY FEATURES

- HIGH PERFORMANCE PREMIUM GREASE TECHNOLOGY
- OUTSTANDING BEARING WEAR PROTECTION EVEN UNDER EXTREME PRESSURE OPERATING CONDITIONS
- ENHANCED RESISTANT TO SHOCK LOADING
- SUITABLE FOR HIGH TEMPERATURES AND WHERE RESISTANCE TO WATER WASH OFF IS REQUIRED
- OUTSTANDING CORROSION PROTECTION OF COMPONENTS
- EXCELLENT OXIDATION RESISTANCE PROVIDES LONG GREASE LIFE

DIRECTIONS FOR USE

MAY BE APPLIED MANUALLY, BY USING A STANDARD GREASE GUN (400g CARTRIDGES AVAILABLE), OR VIA A CENTRALISED LUBRICATION SYSTEM CAPABLE OF PUMPING AN NLGI #2 GREASE. AS WITH ALL GREASES, WHEN USED FOR THE FIRST TIME, CHECK COMPATIBILITY WITH THE PREVIOUS GREASE AND PURGE BEARINGS IF NECESSARY.

AS A GENERAL RULE, TAKE CARE NOT TO OVER-LUBRICATE AND ONLY APPLY THE QUANTITY OF GREASE RECOMMENDED BY THE BEARING MANUFACTURER.

PHYSICAL & CHEMICAL CHARACTERISTICS

PROPERTY	METHOD	UoM	TYPICAL	LIMITS
CONSISTENCY	NLGI	-	2	-
THICKENER	-	-	LITHIUM COMPLEX	-
BASE OIL KINEMATIC VISCOSITY @ 40°C	ASTM D445	mm ² /s	210	-
WORKED PENETRATION (60X)	ASTM D217	0.1mm	280	265-295
DROP POINT	ASTM D2265	°C	260	-
FOUR BALL WELD LOAD	ASTM D2596	KG	300	-
TEMPERATURE RANGE	-	°C	-30 TO +150 (180 INTERMITTENT)	-
COPPER CORROSION	ASTM D130	-	PASS	-
APPEARANCE	ASTM D4176-1	-	CLEAR & BRIGHT	-
COLOUR	VISUAL	-	BLUE	-

Syntol Lubricants

Moss Hall, Moss Hall Lane, Warrington, Cheshire, WA4 4PB, United Kingdom

Tel: 0333 577 1226 Email: sales@syntol-lubricants.com

Web: www.syntol-lubricants.com

