

TERRA-MAX STOU 10W-40



SUPER UNIVERSAL TRACTOROIL

PREMIUMMULTI-FUNCTIONAL TECHNOLOGY

HIGH PERFORMANCE SUPER UNIVERSAL TRACTOR OIL DEVELOPED FROM DECADES OF EXPERIENCE IN CONJUNCTION WITH ORIGINAL EQUIPMENT MANUFACTURERS.

THE USE OF OUR PROPRIETARY BASE OIL TECHNOLOGY, ALONG WITH INNOVATIVE ADDITIVE CHEMISTRY GUARANTEES LONG OIL LIFE AND PERFORMANCE WITHOUT ANY COMPROMISE OF EQUIPMENT RELIABILITY.

APPLICATIONS

DESIGNED FOR ALL SEVERE DUTY OFF-HIGHWAY EQUIPMENT, WHERE A SINGLE OIL IS USED IN ENGINE, TRANSMISSION, HYDRAULICS, AND DIFFERENTIALS (INCLUDING THOSE FITTED WITH OIL IMMERSED (WET) BRAKES, WHERE PERFORMANCE SPECIFICATIONS AND VISCOSITY GRADE ARE APPROPRIATE.

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

NOT SUITABLE FOR USE IN ENGINES FITTED WITH DIESEL PARTICULATE FILTER.

KEY FEATURES

- HIGH PERFORMANCE PREMIUMMULTI-FUNCTIONAL TECHNOLOGY
- SPECIAL ADDITIVES INCLUDED TO ENSURE OUTSTANDING WET BRAKE PERFORMANCE
- STAYS IN VISCOSITY GRADE FOR ENTIRE DRAIN INTERVAL
- HELPS PREVENT DIRT AND SLUDGE BUILD UP TO MAINTAIN ENGINE RESPONSIVENESS, REDUCE VIBRATION AND KEEP EQUIPMENT QUIET
- EXCELLENT OXIDATION RESISTANCE PROVIDES LONG OIL LIFE

PERFORMANCE SPECIFICATIONS & SYNTOL RECOMMENDATIONS

ACEA	E3
API	GL-4, CG-4
CASE	MS 1204, 1206
CATERPILLAR	TO-2
DENISON	HF-0/ 1/ 2
FORD	M2C 41-B, 48-B, 53-A, 86-B, C, 134-A, 134-B, 134-C, 134-D, 159-B, 159-C
JOHN DEERE	J20 A, B, C
MAN	M271
MASSEY FERGUSON	M1135 / 1139/ 1144 / 1145
MERCEDES BENZ	227.1, 228.1
VICKERS	M230-S, M2950S, I-280-S
ZF	TE-ML 06B, 06C, 07B, 07D

PHYSICAL & CHEMICAL CHARACTERISTICS

PROPERTY	METHOD	UoM	TYPICAL	LIMITS
VISCOSITY GRADE	SAE J300	-	10W-40	-
RELATIVE DENSITY @ 15°C	ASTM D4052	g/cm ³	0.870	-
KINEMATIC VISCOSITY @ 40°C	ASTM D445	mm ² /s	95.50	-
KINEMATIC VISCOSITY @ 100°C	ASTM D445	mm ² /s	13.80	12.5 < 16.3
VISCOSITY INDEX	ASTM D2270	-	148	-
POUR POINT	ASTM D97	°C	-36	-30 MAX.
FLASH POINT (CoC)	ASTM D92	°C	210	-
APPEARANCE	ASTM D4176-1	-	CLEAR & BRIGHT	-
COLOUR	VISUAL	-	AMBER	-

Syntol Lubricants

Moss Hall, Moss Hall Lane, Warrington, Cheshire, WA4 4PB, United Kingdom

Tel: 0333 577 1226 Email: sales@syntol-lubricants.com

Web: www.syntol-lubricants.com

