

# TERRA-MAX UTTO 10W-30



## UNIVERSAL TRACTOR TRANSMISSION OIL

### PREMIUM TECHNOLOGY

HIGH PERFORMANCE UNIVERSAL TRACTOR TRANSMISSION OIL DEVELOPED FROM DECADES OF EXPERIENCE IN CONJUNCTION WITH ORIGINAL EQUIPMENT MANUFACTURERS.

THE USE OF OUR PROPRIETARY BASE OIL TECHNOLOGY, ALONG WITH INNOVATIVE ADDITIVE CHEMISTRY GUARANTEES LONG OIL LIFE AND PERFORMANCE WITHOUT ANY COMPROMISE OF EQUIPMENT RELIABILITY.

#### APPLICATIONS

DESIGNED FOR ALL SEVERE DUTY OFF-HIGHWAY EQUIPMENT, WHERE A SINGLE OIL IS USED IN TRANSMISSION, HYDRAULICS, AND DIFFERENTIALS (INCLUDING THOSE FITTED WITH OIL IMMERSED (WET) BRAKES, WHERE PERFORMANCE SPECIFICATIONS AND VISCOSITY GRADE ARE APPROPRIATE.

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

**NOT SUITABLE** FOR USE IN ENGINE APPLICATIONS.

#### KEY FEATURES

- HIGH PERFORMANCE PREMIUM MULTI-FUNCTIONAL TECHNOLOGY
- SPECIAL ADDITIVES INCLUDED TO ENSURE OUTSTANDING WET BRAKE PERFORMANCE
- STAYS IN VISCOSITY GRADE FOR ENTIRE DRAIN INTERVAL
- HELPS PREVENT DIRT AND SLUDGE BUILD UP TO MAINTAIN RESPONSIVENESS, REDUCE VIBRATION AND KEEP EQUIPMENT QUIET
- EXCELLENT OXIDATION RESISTANCE PROVIDES LONG OIL LIFE

#### PERFORMANCE SPECIFICATIONS & SYNTOL RECOMMENDATIONS

AGCO/ ALLIS	821 XL
ALLISON	C-4
API	GL-4
CASE	MS 1204, 1205, 1206, 1207, 1209, 1210
CASE NEW HOLLAND	MAT3510, 3525, 3526
CATERPILLAR	TO-2
DENISON	HF-0/ 1/ 2
FORD	M2C 41-B, 48-B, 53-A, 86-B, C, 134-A, 134-B, 134-C, 134-D
JOHN DEERE	J20 A, B, C
KOMATSU	AXO80
KUBOTA	UDT
MASSEY FERGUSON	M1135/ 1141 / 1143/ 1145
NEW HOLLAND	410-B
VICKERS	M230-S, M2950S, I-280-S
VOLVO	WB101
ZF	TE-ML 03E, 05F, 06K, 17E, 21F

SUITABLE FOR USE IN DEUTZ, FENDT, LANDINI, RENAULT, SAME-LAMBORGHINI.

#### PHYSICAL & CHEMICAL CHARACTERISTICS

PROPERTY	METHOD	UoM	TYPICAL	LIMITS
VISCOSITY GRADE	SAE J300	-	10W-30	-
RELATIVE DENSITY @ 15°C	ASTM D4052	g/cm <sup>3</sup>	0.868	-
KINEMATIC VISCOSITY @ 40°C	ASTM D445	mm <sup>2</sup> /s	69.00	-
KINEMATIC VISCOSITY @ 100°C	ASTM D445	mm <sup>2</sup> /s	10.70	9.3 < 12.5
VISCOSITY INDEX	ASTM D2270	-	144	-
POUR POINT	ASTM D97	°C	-36	-30 MAX.
FLASH POINT (CoC)	ASTM D92	°C	210	-
APPEARANCE	ASTM D4176-1	-	CLEAR & BRIGHT	-
COLOUR	VISUAL	-	AMBER	-

**Syntol Lubricants**

Moss Hall, Moss Hall Lane, Warrington, Cheshire, WA4 4PB, United Kingdom

Tel: 0333 577 1226 Email: [sales@syntol-lubricants.com](mailto:sales@syntol-lubricants.com)

Web: [www.syntol-lubricants.com](http://www.syntol-lubricants.com)

