

# TRAN-SYN ATF MV6

## AUTOMATIC TRANSMISSION FLUID

### 100% SYNTHETIC TECHNOLOGY

HIGH PERFORMANCE MULTI-VEHICLE ATF DEVELOPED FROM DECADES OF EXPERIENCE IN CONJUNCTION WITH ORIGINAL EQUIPMENT MANUFACTURERS. THE USE OF OUR PROPRIETARY BASE OIL TECHNOLOGY, ALONG WITH INNOVATIVE ADDITIVE CHEMISTRY GUARANTEES LONG OIL LIFE WITHOUT ANY COMPROMISE OF EQUIPMENT RELIABILITY.



#### APPLICATIONS

DESIGNED FOR NORMAL & SEVERE DUTY EUROPEAN, US & ASIAN CAR, TRUCK & OFF-HIGHWAY AUTOMATIC TRANSMISSIONS & POWER STEERING UNITS WHERE PERFORMANCE SPECIFICATIONS AND VISCOSITY GRADE ARE APPROPRIATE. ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

#### KEY FEATURES

- HIGH PERFORMANCE PREMIUM MULTI-VEHICLE TECHNOLOGY
- OUTSTANDING TRANSMISSION WEAR PROTECTION
- MAINTAINS CORRECT FRICTIONAL CHARACTERISTICS FOR ENTIRE DRAIN INTERVAL
- HELPS PREVENT DEPOSIT BUILD UP AS A RESULT OF DEDICATED ATF TECHNOLOGY
- EXCELLENT OXIDATION RESISTANCE PROVIDES LONG OIL LIFE

#### PERFORMANCE SPECIFICATIONS & SYNTOL RECOMMENDATIONS

AISIN WARNER	AW-1, JWS 3324
APOLLOIL/KIA	ATF RED-1K
BMW	PART #83 22 0 397 114, LT 71141, LA2634, 7045-E, ETL-8072B
CHRYSLER	PART #68043742AA, ATF +4, ATF +3
ESSO	TYPE LT 71141 ATF
FORD	MERCON, MERCON LV, SP, V
GM	DEXRON VI, IIIH, IIIIG, IIE, IID, TYPE A SUFFIX A (TASA)
HONDA/ACURA	DW-1 & Z-1
HYUNDAI/KIA	GENUINE ATF, SP-II, SP-III, SP-IV, SPH-IV & NWS-9638 T-5
IDEMITSU	K17
ISUZU	SCS, GENUINE ATF
JASO	1A
MAZDA	ATF M-III and ATF M-V
MERCEDES BENZ	MB 236.17, 236.16, 236.15, 236.14, 236.12, 236.11, 236.10, 236.9, 236.8, 236.7, 236.6, 236.5, 236.41
MITSUBISHI	ATF-J2, ATF-J3, SP-II, SP-III, SP-IV
MOPAR	PART #05189966AA (AS68RC)
NISSAN/INFINITI	MATIC D/K/J, MATIC S
SHELL	ATF 3403-M115, LA2634, M1375.4
SUBARU	ATF, ATF-HP, ATF 5AT
TEXACO	7045-E, ETL-8072B, N402
TOYOTA/LEXUS	TYPE T-III, TYPE T-IV, TYPE WS
VOITH	H55.6335.xx (G607)
VOLKSWAGEN/AUDI	PART #G 052 025/540 (A2) #G 055 025/990 (A2)
VOLVO	PART # 1161521, 1161540/1161640
ZF	LIFEGUARD FLUID 6, LIFEGUARD FLUID 8, LIFEGUARD FLUID 9

#### PHYSICAL & CHEMICAL CHARACTERISTICS

PROPERTY	METHOD	UoM	TYPICAL	LIMITS
VISCOSITY GRADE	SAE J306	-	-	-
RELATIVE DENSITY @ 15°C	ASTM D4052	g/cm <sup>3</sup>	0.846	-
KINEMATIC VISCOSITY @ 40°C	ASTM D445	mm <sup>2</sup> /s	29.80	-
KINEMATIC VISCOSITY @ 100°C	ASTM D445	mm <sup>2</sup> /s	6.00	5.8-6.2
VISCOSITY INDEX	ASTM D2270	-	206	-
POUR POINT	ASTM D97	°C	-45	-
FLASH POINT (CoC)	ASTM D92	°C	210	-
BROOKFIELD VISCOSITY (-40°C)	ASTM D2983	mPa.s	9,000	20,000 MAX.
APPEARANCE	ASTM D4176-1	-	CLEAR & BRIGHT	-
COLOUR	VISUAL	-	AMBER	-

**Syntol Lubricants**

Moss Hall, Moss Hall Lane, Warrington, Cheshire, WA4 4PB, United Kingdom

Tel: 0333 577 1226 Email: sales@syntol-lubricants.com

Web: www.syntol-lubricants.com

