

TRAN-SYN ATF MV3



HEAVY DUTY AUTOMATIC TRANSMISSION FLUID

100% SYNTHETIC TECHNOLOGY

HIGH PERFORMANCE MULTI-VEHICLE ATF DEVELOPED FROM DECADES OF EXPERIENCE IN CONJUNCTION WITH ORIGINAL EQUIPMENT MANUFACTURERS.

THE USE OF OUR PROPRIETARY BASE OIL TECHNOLOGY, ALONG WITH INNOVATIVE ADDITIVE CHEMISTRY GUARANTEES LONG OIL LIFE WITHOUT ANY COMPROMISE OF EQUIPMENT RELIABILITY.

APPLICATIONS

DESIGNED FOR SEVERE DUTY EUROPEAN, US & ASIAN CAR, TRUCK & OFF HIGHWAY AUTOMATIC TRANSMISSIONS & POWER STEERING UNITS WHERE PERFORMANCE SPECIFICATIONS AND VISCOSITY GRADE ARE APPROPRIATE.

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

KEY FEATURES

- HIGH PERFORMANCE PREMIUM MULTI-VEHICLE TECHNOLOGY
- OUTSTANDING TRANSMISSION WEAR PROTECTION
- MAINTAINS CORRECT FRICTIONAL CHARACTERISTICS FOR ENTIRE DRAIN INTERVAL
- HELPS PREVENT DEPOSIT BUILD UP AS A RESULT OF DEDICATED ATF TECHNOLOGY
- EXCELLENT OXIDATION RESISTANCE PROVIDES LONG OIL LIFE

PERFORMANCE SPECIFICATIONS / SUITABLE FOR USE

AISIN-WARNER	JWS 3309 (MOBIL ATF 3309)
ALLISON	C4, TES 295, TES 389
BMW (INCL. MINI)	PART #81 22 9 400 272/275, #81 22 9 407 858/859, #83 22 0 024 249/359, #83 22 0 026 922, #83 22 0 402 413, #83 22 0 403 248/249, #83 22 7 542 290, #83 22 7 407 765/807
CHRYSLER	ATF +4, ATF +3, ATF +2, ATF +, AS68RC ATF, SP-III
ESSO	LT 71141
FORD	MERCON, MERCON V, XT-2-QDX, XT-2-QSM, XT-5-QM/DM, XT-8-QAW, XT-9-QMM5, WSS-M2C922-A1
GM /OPEL	DEXRON IIIH, IIIG, IIE, IID, TYPE A SUFFIX A (TASA), TYPE T-IV, PART #12378515, #1940700, #1940767, #21005966, #22717466, #88900925, #9986915
HONDA/ACURA	Z-1
HYUNDAI/KIA	ATF RED-1K, GENUINE ATF, SP-II, SP-III, SP-IV, JWS 3309 T-4, #UM040 CH20 RED-1
IDEMITSU	ATF HP, ATF K17
ISUZU	ATF II, ATF III, SCS, GENUINE ATF, PART #082009001
JAGUAR LAND ROVER	JLM 20238, JLM 20292, JLM 21044, K17, WSS-M2C-922-A1
JASO	1A
MAN	339
MAZDA	ATF M-III, ATF M-V, ATF TYPE T-IV, F1, JWS 3317, M-5 PART #XT-9-QMM5
MERCEDES BENZ	MB 236.11, 236.10, 236.9, 236.8, 236.7, 236.6, 236.5
MITSUBISHI	ATF-J2, SP PART #MS991156, SP-II, SP-III
NISSAN/INFINITI	N402, MATIC D/J/K
PEUGEOT-CITROEN (PSA)	PART # Z000169756
PORSCHE	PART #000 043 204 41, #000 043 205 09, #000 043 205 28, #999 917 547 00(A2)
RENAULT	MATIC D2
RENK	RENK GENUINE OIL
SAAB	ATF 3309 T-IV
SHELL	ATF 3403-M115, LA2634
SUBARU	ATF-HP, PART #K0140Y0700
SUZUKI	3309, 3317
SSANG YONG	DSIH 5M-66
TEXACO	ETL 7045E, ETL 8072B, N402
TOYOTA/LEXUS	TYPE T-III, TYPE T-IV
VOLKSWAGEN/AUDI	PART #G 052 025 (A2) #G 052 990 (A2), #G 055 025 (A2), #G 052 055 (A2), #G 052 162 (A1, A2), #G US 000 162
VOLVO	PART # 1161521, 1161540/1161640, VCE 1273.41
ZF	TE-ML 11A, 11B, LIFEGUARD FLUID 5

MEETS OVER 100 OEM SPECIFICATIONS – PLEASE CONTACT US TO CHECK YOUR SPECIFIC REQUIREMENT.

PHYSICAL & CHEMICAL CHARACTERISTICS

PROPERTY	METHOD	UoM	TYPICAL
VISCOSITY GRADE	SAE J306	-	-
RELATIVE DENSITY @ 15°C	ASTM D4052	g/cm ³	0.876
KINEMATIC VISCOSITY @ 40°C	ASTM D445	mm ² /s	34.00
KINEMATIC VISCOSITY @ 100°C	ASTM D445	mm ² /s	7.80
VISCOSITY INDEX	ASTM D2270	-	208
POUR POINT	ASTM D97	°C	-42
FLASH POINT (CoC)	ASTM D92	°C	204
BROOKFIELD VISCOSITY (-40°C)	ASTM D2983	mPa.s	17,000
APPEARANCE	ASTM D4176-1	-	CLEAR & BRIGHT
COLOUR	VISUAL	-	AMBER

Syntol Lubricants

Moss Hall, Moss Hall Lane, Warrington, Cheshire, WA4 4PB, United Kingdom
 Tel: 0333 577 1226 Email: sales@syntol-lubricants.com
 Web: www.syntol-lubricants.com

