

HYDRA-MAX HM 68

HEAVY DUTY HYDRAULIC OIL

PREMIUM TECHNOLOGY

HIGH PERFORMANCE HYDRAULIC OIL DEVELOPED FROM DECADES OF EXPERIENCE IN CONJUNCTION WITH ORIGINAL EQUIPMENT MANUFACTURERS.

THE USE OF OUR PROPRIETARY BASE OIL TECHNOLOGY, ALONG WITH INNOVATIVE ADDITIVE CHEMISTRY GUARANTEES LONG OIL LIFE WITHOUT ANY COMPROMISE OF EQUIPMENT RELIABILITY.

SYNTOL
LUBRICANTS

APPLICATIONS

DESIGNED FOR NORMAL & SEVERE DUTY HYDRAULIC SYSTEMS WHERE A ZINC CONTAINING MINERAL OIL IS REQUIRED. SUCH SYSTEMS ARE COMMONLY FOUND IN INDUSTRIAL APPLICATIONS, MOBILE PLANT, CONSTRUCTION AND AGRICULTURAL EQUIPMENT.

ALWAYS REFER TO EQUIPMENT HANDBOOK / OPERATING MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

NOT SUITABLE FOR USE IN SYSTEMS WHERE SILVER PLATED COMPONENTS OR ASHLESS (ZINC FREE) HYDRAULIC OILS ARE REQUIRED. PLEASE CONSULT US FOR A RECOMMENDATION FOR SUCH SYSTEMS.

KEY FEATURES

- HIGH PERFORMANCE PREMIUM HYDRAULIC OIL TECHNOLOGY
- OUTSTANDING PUMP WEAR PROTECTION
- STAYS IN VISCOSITY GRADE FOR ENTIRE DRAIN INTERVAL
- OUTSTANDING SEAL COMPATIBILITY TO HELP REDUCE LEAKS AND OIL LOSS
- EXCELLENT OXIDATION RESISTANCE PROVIDES LONG OIL LIFE

PERFORMANCE SPECIFICATIONS

AFNOR	NF-E 48-603
ASTM	D6158 HM
DIN	51524 PARTS 1 & 2
GB	11118.1-2011 L-HM
ISO	6743-4 HM, 11158 HM
JCMAS	P041 HK
SAE	MS1004 HM
AIST US STEEL	126, 127
BOSCH REXROTH	RDE 90235 (90245), 90220
EATON	E-FDGN-TB002-E
FIVES (CINCINNATI)	P69
GM	LS-2
PARKER (DENISON)	HF-0, HF-1, HF-2
SEB	181222

PHYSICAL & CHEMICAL CHARACTERISTICS

PROPERTY	METHOD	UoM	TYPICAL	LIMITS
VISCOSITY GRADE	ISO VG	-	68	-
RELATIVE DENSITY @ 15°C	ASTM D4052	g/cm3	0.870	-
KINEMATIC VISCOSITY @ 40°C	ASTM D445	mm2/s	68.0	61.2 – 74.8
KINEMATIC VISCOSITY @ 100°C	ASTM D445	mm2/s	8.8	-
VISCOSITY INDEX	ASTM D2270	-	102	95 MIN.
POUR POINT	ASTM D97	°C	-30	-20°C MAX.
FLASH POINT (CoC)	ASTM D92	°C	225	190°C MIN.
FOAMING TENDENCY (SEQUENCE I, III, III)	ASTM D892	mL	0/0, 0/0, 0/0	50/0, 50/0, 50/0
APPEARANCE	ASTM D4176-1	-	CLEAR & BRIGHT	-
COLOUR	VISUAL	-	AMBER	-

Syntol Lubricants

Moss Hall, Moss Hall Lane, Warrington, Cheshire, WA4 4PB, United Kingdom

Tel: 0333 577 1226 Email: sales@syntol-lubricants.com

Web: www.syntol-lubricants.com

