

TRANSYN MTF ULV



ULTRA LOW VISCOSITY MANUAL TRANSMISSION FLUID

100% SYNTHETIC TECHNOLOGY

HIGH PERFORMANCE ULTRA LOW VISCOSITY MTF FLUID DEVELOPED FROM DECADES OF EXPERIENCE IN CONJUNCTION WITH ORIGINAL EQUIPMENT MANUFACTURERS.

THE USE OF OUR PROPRIETARY BASE OIL TECHNOLOGY, ALONG WITH INNOVATIVE ADDITIVE CHEMISTRY GUARANTEES LONG OIL LIFE WITHOUT ANY COMPROMISE OF EQUIPMENT RELIABILITY.

APPLICATIONS

DESIGNED FOR NORMAL & SEVERE DUTY EUROPEAN, US & ASIAN VEHICLE PASSENGER CAR MANUAL TRANSMISSIONS WHERE PERFORMANCE SPECIFICATIONS AND VISCOSITY GRADE ARE APPROPRIATE.

ALWAYS REFER TO VEHICLE HANDBOOK / OWNERS MANUAL FOR RECOMMENDED OIL SPECIFICATION & VISCOSITY GRADE BEFORE USE.

KEY FEATURES

- HIGH PERFORMANCE PREMIUM MTF TECHNOLOGY AND 100% SYNTHETIC PAO BASE OILS
- EXTREMELY HIGH FUEL ECONOMY BENEFIT
- EXCELLENT TRANSMISSION WEAR PROTECTION
- MAINTAINS CORRECT FRICTIONAL CHARACTERISTICS FOR ENTIRE DRAIN INTERVAL
- HELPS PREVENT DEPOSIT BUILD UP AS A RESULT OF HIGH-PERFORMANCE DETERGENT ADDITIVE TECHNOLOGY
- EXCELLENT OXIDATION RESISTANCE PROVIDES LONG OIL LIFE

PERFORMANCE SPECIFICATIONS & SYNTOL RECOMMENDATIONS

BOT	233 LVX
HYUNDAI/KIA	04300-2N100 WDGO-1, 04300-KX1B0
KIA	UM015-CH080
VAG	VW G052 549 A2

PHYSICAL & CHEMICAL CHARACTERISTICS

PROPERTY	METHOD	UoM	TYPICAL	LIMITS
VISCOSITY GRADE	SAE J306	-	70W	-
RELATIVE DENSITY @ 15°C	ASTM D4052	g/cm3	0.847	-
KINEMATIC VISCOSITY @ 40°C	ASTM D445	mm2/s	23.00	-
KINEMATIC VISCOSITY @ 100°C	ASTM D445	mm2/s	5.60	5.4 – 5.8
VISCOSITY INDEX	ASTM D2270	-	199	-
POUR POINT	ASTM D97	°C	<-60	-
APPEARANCE	ASTM D4176-1	-	CLEAR & BRIGHT	-
COLOUR	VISUAL	-	AMBER	-

